Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Overall Beldfoil® Shield

Audio, Control and Instrumentation Cables
Plenum-Rated and Non-Plenum

Jameco Part Number 234186 (8760-060-500)

18 AWG Stranded Conductors (16x30) • Tinned Copper • Twisted Pair • Overall 100% Beldfoil Shield • 20 AWG Stranded TC Drain Wire

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths Ft.	Standard Lengths m	Standard Unit Weight Lbs.	Standard Unit Weight kg	Insulation Thickness Inch	Insulation Thickness mm	Jacket Thickness Inch	Jacket Thickness mm	Nominal OD Inch	Nominal OD mm	Nominal Capacitance * pF/ Ft.	Nominal Capacitance * pF/ m	Nominal Capacitance ** pF/ Ft.	Nominal Capacitance ** pF/ m
Polyethylene Insulation • Chrome PVC Jacket																		
UL AWM Style 2092 (300V 60°C)  Shorting Fold	**8760**	NEC: CM CEC: CM	1	Black, Clear	250 U-500 500 U-1000 1000 2000 5000 10000	76.2 U-152.4 152.4 U-304.8 304.8 609.6 1524.0 3048.0	6.8 13.0 13.0 26.0 25.0 50.0 135.0 260.0	3.1 5.9 5.9 11.8 11.4 22.7 61.4 118.2	.019	.48	.028	.71	.222	5.64	24	79	44	144
	9460	NEC: CM CEC: CM	1	Black, Clear	U-500 U-1000	U-152.4 U-304.8	18.5 36.0	8.4 16.4	.019	.48	.030	.76	.230	5.84	24	79	44	144

For Plenum versions of 8760, see 88760, 87760 or 82760.

The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is on the inside of foil shield.

18 AWG Stranded Conductors (19x30) • Tinned Copper • Twisted Pair • Overall 100% Beldfoil Shield • 20 AWG Stranded TC Drain Wire

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths Ft.	Standard Lengths m	Standard Unit Weight Lbs.	Standard Unit Weight kg	Insulation Thickness Inch	Insulation Thickness mm	Jacket Thickness Inch	Jacket Thickness mm	Nominal OD Inch	Nominal OD mm	Nominal Capacitance * pF/ Ft.	Nominal Capacitance * pF/ m	Nominal Capacitance ** pF/ Ft.	Nominal Capacitance ** pF/ m
Plenum • FEP Insulation • Red FEP Jacket																		
300V RMS, Non-conduit  Z-Fold®	**88760**	NEC: CMP CEC: CMP FT6	1	Black, Red	100 U-500 500† U-1000 1000†	30.5 U-152.4 152.4 U-304.8 304.8	3.7 12.5 13.0 24.0 24.0	1.7 5.7 5.9 10.9 10.9	.007	.18	.014	.36	.150	3.81	51	167	97	318
Plenum • FEP Insulation • Red Fluorocopolymer Jacket																		
300V RMS, Non-conduit  Z-Fold®	**87760**	NEC: CMP CEC: CMP FT6	1	Black, Red	U-500 500† 1000†	U-152.4 152.4 304.8	12.0 12.5 23.0	5.5 5.7 10.5	.007	.18	.014	.36	.150	3.81	51	167	97	318
Plenum • FEP Insulation • Natural Flamarrest® Jacket																		
300V RMS, Non-conduit  Z-Fold®	**82760**	NEC: CMP CEC: CMP FT6	1	Black, Red	U-500† U-1000† 1000†	U-152.4 U-304.8 304.8	11.5 22.0 23.0	5.2 10.0 10.5	.007	.18	.014	.36	.150	3.81	51	167	97	318

TC = Tinned Copper

*Capacitance between conductors.
**Capacitance between one conductor and other conductors connected to shield.
†Spools and/or UnReel® cartons are one piece, but length may vary ±10% for spools and ±5% for UnReel from length shown.